

► Çok Tüplü, Tek Kılıflı Zırhlı Havai Fiber Optik Kablo (MLT SM-MM SJSA FIG.8)



PHYSICAL DESCRIPTION

- 4-8-12-16-24-36-48-72 fibers armored outdoor aerial figure 8 fiber optic cable,
- Thixotropic jelly filled loose tubes,
- Loose tubes and filler (if any) are SZ stranded around the non- metallic central strength member (FRP),
- Jelly filled core,
- Polyester tape as core wrap,
- Corrugated steel armor,
- Outer jacket is made of medium density polyethylene,
- Ripcord is inserted for easy jackets removal.

DESCRIPTION

| | |
|-----------------------------|--|
| Fiber Type | SM & MM Fibers |
| Central strength member | All-dielectric FRP |
| Tube material | PBT (Polybutylene Terephthalate) |
| Color of loose tubes | Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua |
| Color of fibers in per tube | Blue, Orange, Green, Brown, Slate, White |
| Tube filling compound | Thixotropic jelly |
| Core filling compound | Jelly |
| Ripcord | Aramid cord |
| Tape wrap | Polyester tape |
| Armor | Corrugated steel tape |
| Outer jacket | Black MDPE, thickness nominal 1.5 ± 0.1 mm (cable and messenger wire) |
| Web | Height: 2.5 ± 0.5 mm Width: 2.5 ± 0.5 mm |
| Messenger Wire | Steel; $7 \times 1.32 \pm 0.1$ mm |
| Surface Marking | As a customer request |

| Fiber Count | Number of Tube | Nuber of Filler | Number of fiber in per tube | Central Strength Member OD(mm) | Central strength Member OD(mm) | Tube Out-er/Inner Diameter(mm) | Cable Diameter(mm) | Cable Weight(kg/ km) |
|-------------|----------------|-----------------|-----------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------|----------------------|
| 4 | 1 | 5 | 4 | 2.2 | N/A | 2.0/1.4* | 11.7/21.2* | 250* |
| 8 | 2 | 4 | 4 | 2.2 | N/A | 2.0/1.4* | 11.7/21.2* | 251* |
| 12 | 3 | 3 | 4 | 2.2 | N/A | 2.0/1.4* | 11.7/21.2* | 252* |
| 16 | 4 | 2 | 4 | 2.2 | N/A | 2.0/1.4* | 11.7/21.2* | 252* |
| 24 | 6 | - | 4 | 2.2 | N/A | 2.0/1.4* | 11.7/21.2* | 253* |
| 36 | 6 | - | 6 | 2.2 | N/A | 2.0/1.4* | 11.7/21.2* | 253* |
| 48 | 6 | - | 8 | 2.5 | N/A | 2.4/1.7* | 12.8/22.3* | 280* |
| 72 | 6 | - | 12 | 2.5 | N/A | 2.4/1.7* | 12.8/22.3* | 281* |

*:Tolerance is $\pm 10\%$

Mechanical and Environmental Properties

| Physical tests | Value | Standart |
|--|---|------------------|
| Tensile Strength | 5000 N (during Installation) 2500 N (during Operation) | IEC 60794-1-E1 |
| Impact Resistance | 10J, 3 impacts | IEC 60794-1-E4 |
| Crush Resistance | 220 N/cm | IEC 60794-1-E3 |
| Temperature Cycling | -40 to +70 °C | IEC 60794-1-F1 |
| Bend Radius (during installation) | 20x cable diameter | IEC 60794-1-E11 |
| Bend Radius (during Service) | 10x cable diameter | IEC 60794-1-E11 |
| Repeating Bending | 20x cable diameter between | IEC 60794-1-2 E6 |
| Operation Temperature | -40 to +70 C | |
| Storage and Transportation Temperature | -40 to +70 C | |
| Installation Temperature | -30 to +60 C | |
| Reel Marking | As a customer request | |

STANDART SM FIBER ITU-T G 652 D

| PROPERTIES | SPECIFIED Value |
|-------------------------------|--|
| Attenuation (max) | 0.40 dB/km (1310 nm) 0.25 dB/km (1550 nm) |
| MFD | 9.2±0.4 µm (1310 nm) 10.4±0.5 µm (1550 nm) |
| Chromatic Dispersion (max) | 3.5 ps/(nmxkm)(1310 nm) 18 ps/(nmxkm)(1550 nm) |
| Cladding diameter | 125 ± 0.3 µm |
| Core/Clad Concentricity error | ≤ 0.5 µm |
| Zero dispersion wavelength | 1300nm ≤ ≤1324nm |
| Cladding non-circularity | ≤ 0.7 % |
| Coating diameter | 245 ± 10 µm |
| Cut Off Wavelength | ≤ 1260nm |
| Proof Test | ≥ 1% (100kpsi or 0.7GPa) |

STANDARD SM FIBER ITU-T G 657 A

| PROPERTIES | SPECIFIED Value |
|--|---|
| Attenuation (max) | 0.40 dB/km (1310 nm) 0.25 dB/km (1550 nm) |
| MFD | 9.0±0.4 µm (1310 nm) 10.1±0.5 µm (1550 nm) |
| Cladding diameter | 125±0.7µm |
| Core/Clad Concentricity error (max) | 0.5 µm |
| Zero dispersion wavelength | 1300nm ≤ ≤1324nm |
| Cladding non-circularity (max) | % 0.7 |
| Coating diameter | 242±7 µm |
| Cut Off Wavelength | ≤1260nm |
| Proof Tensile Test | ≥ 1% (100kpsi or 0.7GPa) |
| Macro bending Attenuation : (10 turn on a 15 mm radius mandrel) | ≤ 0.25 dB @1550 nm |

SM FIBER ITU-T G 657 A2 Bend Insensitive

| PROPERTIES | SPECIFIED Value |
|--|---|
| Attenuation (max) | 0.35 dB/km (1310 nm) 0.22 dB/km (1550 nm) |
| MFD | 8.6 ± 0.4 μm (1310 nm) |
| Cladding diameter | 125 ± 0.7 μm |
| Core/Clad Concentricity error (max) | 0.5 μm |
| Zero dispersion wavelength | 1302nm ≤ ≤1322nm |
| Cladding non-circularity (max) | % 1 |
| Coating diameter | 240 ± 5 μm |
| Cut Off Wavelength | ≤ 1260nm |
| Proof Tensile Test | ≥ 1% (100kpsi or 0.7GPa) |
| Macro bending Attenuation : (1 turn on a 7.5 mm radius mandrel) | ≤ 0.5 dB @1550 nm |

NON-ZERO DISPERSION SHIFTED SM FIBER ITU-T G 655

| PROPERTIES | SPECIFIED Value |
|--------------------------------------|--------------------------|
| Attenuation (max) | 0.25 dB/km (1550 nm) |
| MFD | 9.6 ± 0.4 μm (1550 nm) |
| Chromatic Dispersion at 1530–1565 nm | 2.0–6.0 ps/(nmxkm)nm) |
| Chromatic Dispersion at 1565–1625 nm | 4.0–12.0 ps/(nmxkm) |
| Cladding diameter | 125 ± 0.7 μm |
| Core/Clad Concentricity error (max) | 0.6 μm |
| Cladding non-circularity (max) | % 0.7 |
| Coating diameter | 245 ± 5 nm |
| Cut Off Wavelength | ≤ 1450nm |
| Proof Test | ≥ 1% (100kpsi or 0.7GPa) |

62.5/125 μm MM OM1 OPTICAL FIBER

| PROPERTIES | SPECIFIED Value |
|-------------------------------|--|
| Attenuation (max) | 3.5 dB/km (850 nm) 1.5 dB/km (1300 nm) |
| Bandwidth (min) | 200 MHz.km(850 nm) 600 MHz.km(1300 nm) |
| Numerical Aparature | 0.275±0.015 |
| Core Diameter | 62.5 ± 2 μm |
| Cladding Diameter | 125 ± 1 μm |
| Core/Clad Concentricity error | ≤ 1 μm |
| Cladding non-circularity | ≤ 0.7 % |
| Coating Diameter | 242 ± 5 μm |
| Proof Test | ≥ 100kpsi or 0.7GPa |

50/125 µm MM OM2 OPTICAL FIBER

| PROPERTIES | SPECIFIED Value |
|-------------------------------|--|
| Attenuation (max) | 3.5 dB/km (850 nm) 1.5 dB/km (1300 nm) |
| Bandwidth (min) | 700 MHz.km(850 nm) 500 MHz.km(1300 nm) |
| Numerical Aparature | 0.200±0.015 |
| Core Diameter | 50 ± 2 µm |
| Cladding Diameter | 125 ± 1µm |
| Core/Clad Concentricity error | ≤ 1 µm |
| Cladding non-circularity | ≤ 0.7 % |
| Coating Diameter | 242 ± 5 µm |
| Proof Test | ≥ 100kpsi or 0.7GPa |

50/125 µm MM OM3 OPTICAL FIBER

| PROPERTIES | SPECIFIED Value |
|-------------------------------|---|
| Attenuation (max) | 3.5 dB/km (850 nm) 1.5 dB/km (1300 nm) |
| Bandwidth (Laser EMB) | 2000 MHz.km(850 nm) 500 MHz.km(1300 nm) |
| Bandwidth (Overfilled) | 1500 MHz.km(850 nm) 500 MHz.km(1300 nm) |
| Numerical Aparature | 0.200±0.015 |
| Core Diameter | 50 ± 2 µm |
| Cladding Diameter | 125 ± 1µm |
| Core/Clad Concentricity error | ≤ 1 µm |
| Cladding non-circularity | ≤ 0.7 % |
| Coating Diameter | 242 ± 5 µm |
| Proof Test | ≥ 100kpsi or 0.7GPa |

50/125 µm MM OM4 OPTICAL FIBER

| PROPERTIES | SPECIFIED Value |
|-------------------------------|---|
| Attenuation (max) | 3.0 dB/km 1.0 dB/km |
| Bandwidth (Laser EMB) | 4700 MHz.km(850 nm) 500 MHz.km(1300 nm) |
| Bandwidth (Overfilled) | 3500 MHz.km(850 nm) 500 MHz.km(1300 nm) |
| Numerical Aparature | 0.2±0.015 |
| Core Diameter | 50 ± 3µm |
| Cladding Diameter | 125 ± 3µm |
| Core/Clad Concentricity error | ≤ 1 µm |
| Cladding non-circularity | ≤ 0.7 % |
| Coating Diameter | 242 ± 5 µm |
| Proof Test | ≥ 100kpsi or 0.7GPa |





